

Series 3 HT-6 and HT-12 evaporators



The all new Series 3 HT-6 and HT-12 evaporators from Genevac

Building on Genevac's pedigree of evaporation expertise, these systems represent the ultimate in solvent evaporation technology. New sleek lines and latest touch screen technology make optimising your evaporation processes effortless. Developed by Genevac's expert team in response to customer demands, these evaporation systems feature:

- Rugged design with clean lines and a modern look
- New intuitive touchscreen control system for ultimate ease of use
- Integrated condenser meaning a smaller system footprint
- Front opening for easy access. Series 3 HT evaporators feature a new 6 place rotor which accept all existing Genevac holders
- All the features and functionality you expect from a Genevac HT evaporator including Dri-Pure anti-bumping, automatic end of run, HCl resistance, Inert Gas Purge, Lyospeed and **EXALT™** controlled crystallisation

Control Software

The latest touchscreen controls feature intuitive programming with enhanced monitoring and review of the whole evaporation process.

Preset methods for generic solvent groups offer easy "Press and Go" operation, similar to that seen on the EZ-2.

Truly customised auto-programming – methods are designed on board for optimum performance tailored to your specific solvent and sample formats.

Simplified manual programming means you can quickly and easily specify multistage evaporation methods.

User login allows personalisation of method screens and easy access to your favourite methods whilst providing security for data logging

All new and enhanced graphing allows the user to monitor operational parameters both during the run and to review once complete. Increased data logging capacity means you will never lose that critical run data.

USB method and code transfer with easy system back up and set up duplication.



Ergonomic design

The touch screen controls with help functions along with a light touch door and spacious interior combine for ease of operation that can be tailored to suit the user.

Front opening, and new lower height of the Series 3 HT-12, provide for easy, comfortable sample loading

The redesigned chamber, with wipe clean coating, now has fewer obstacles to clean around. Improved chamber heating also eliminates cold spots and subsequent condensation.

An enhanced "reduce odour" function is designed to prevent any offensive or unhealthy exposure to solvent vapour when opening the door.



Infinity Trolley

Infinity Trolley is a modular system, designed to accommodate the full range of Genevac evaporation equipment including the Series 3 HT-12 and HT-6. If required, trolleys can be joined together, side-by-side, creating a HT-24 or HT-36, up to HT-"Infinity", whilst minimising fume hood footprint. The Infinity trolley upper shelf holds the evaporator, whilst the lower shelf will accommodate the pump and waste containers. The unique lower shelf 'truck' can be rolled out to stabilise the trolley for movement, and for easy access to the lower components.

Truck Fully Retracted

- Front feet of Infinity Trolley are lowered
- Trolley is secure for system use and cannot be moved

Truck Fully Extended

- Front feet of the Infinity Trolley are lifted and unit can now be moved
- Extended Truck provides the required stability for movement



Integrated Condenser

The new integrated high power VC7000 condenser chills to -75C and has auto defrost and drain capabilities as standard. Our highest specification condenser to date the VC7000 facilitates enhanced LyoSpeed performance and optimises solvent recovery. The integrated condenser results in a smaller overall system footprint – saving valuable fume hood space.



Sample Holders

To ensure optimum heat transfer, Genevac sample holders are manufactured from high-grade solid aluminium to very close tolerances that ensure tubes fit snugly and are mass balanced during manufacture to ensure smooth running of the evaporator.

A wide range of sample holders enable all common formats to be accommodated with ease.



- Side bridge swings will accommodate a range of sample blocks for tubes and vials
- One piece holders which fit directly onto the rotor are available for larger tubes, bottles and flasks
- FastStack™ microplate holders will accommodate two deep well or four shallow well plates per rotor position

Series 3 HT-6 and HT-12 evaporators will accommodate all existing Genevac sample holders and swings.

SampleGenie™

SampleGenie™ comprises unique flask and sample holder technology which enables large volume samples to be dried or concentrated directly into the small vial of your choice.

Where HPLC purification fractions are used, fractions can be combined into one flask and dried, or fast lyophilised, into the final vial.



SampleGuard

Comprising up to four thermocouples and a Bluetooth® transmitter, the new patented SampleGuard temperature control system provides real time feedback for accurate control of actual sample temperatures.

Either one or two probes can be used to accurately and reliably determine end-of-run, enabling the system to stop automatically.

Probes can be used to measure temperature in the sample and at any point in the sample holder allowing easy optimisation of timed runs and LyoSpeed™ methods.


A new housing system protects the thermocouples from damage thus extending their lifespan and a battery powered Bluetooth® transmitter means the system can operate at all rotor speeds, including Lyospeed.

SampleGuard temperature control gives operators peace of mind by protecting samples from overheating when evaporation is complete and can eliminate time consuming method development.



DriPure®

Genevac's patented Dri-Pure® sample protection system prevents cross-contamination and sample loss due to bumping and is fitted as standard on Series 3 HT evaporators.



- A** New touchscreen control interface
- B** High power lamps
- C** SampleGuard – provides real time feedback for accurate control of actual sample temperatures
- D** Integrated condenser reduces overall system footprint and increases efficiency

High Power Lamps

New high power, long life IR lamps emit no UV and are user changeable, with easy access from the front of the system. Independent rotor layer control further increases lamp life.





Inert gas Purge

When working with highly explosive solvents, such as diethyl ether or pentane, the Inert Gas Purge (IGP) system is mandatory. The new, integrated IGP flushes all the air out of the system before the evaporation process starts, replacing it with an inert gas – nitrogen or argon.

Additionally, the IGP system fills the system with inert gas when the evaporator stops, and can be used to keep sensitive samples under a gas blanket until removed by the operator.



- E** Auto defrost and drain for optimal solvent recovery
- F** Spacious, easy clean chamber
- G** Easy open front door for convenient loading

HCl

When working with the most aggressive solvents such as hydrochloric acid and other acid chlorides, the HCl-resistant option on the Series 3 HT enables unrestricted use and maintains reliability. Key elements of the system are engineered in Hastelloy®, glass or PTFE, to provide full protection against these acids. This 'HCl option' must be specified when ordering, as it cannot be retrofitted.



Fast Lyophilisation

Traditional concentration to dryness in a Genevac evaporator is fast and safe, however for some users a dried film is not the best fit for their requirements. Additionally, when working with certain solvents a fully dried result can be hard to achieve due to interactions with the dissolved sample – resulting in the formation of a gum or oil. Dry powders can be easier to weigh and re-dissolve than a dry film, and so are preferred for some applications.

Genevac developed LyoSpeed™ methods to enable samples to be freeze dried in little more time than by concentrating to dryness. Methods have been specially developed for use with HPLC fractions containing water and acetonitrile, or methanol.

Using Genevac Series 3 HT evaporators, HPLC fractions can be automatically concentrated to a few millilitres and then frozen and rapidly lyophilised to produce a diffuse dry powder, which can easily be re-dissolved or weighed out.



LyoSpeed

Auto Defrost & Drain

Auto-Defrost & Drain, standard on Series 3 HT evaporators, enables fast and efficient evaporation of diverse mixtures of solvents, without compromising solvent recovery. This function enables the system to automatically drain the condenser of volatile solvents between stages in a method, and to fully defrost and drain the system on completion, with no user intervention.

Volatile solvents evaporate first and collect in the condenser. To remove the higher boiling point solvents, low pressures must be achieved however, which can cause the volatile solvent to boil out of the condenser and 'spoil' the vacuum level. Vacuum spoiling, whilst less common on low temperature traps, may well affect final dryness of samples, or in the very worst cases, the ability to evaporate the higher boiling point solvent altogether.

When evaporating HPLC fractions, auto-defrost and drain helps achieve excellent final dryness and improves results when working with any mixture of solvents with differing boiling points.

An additional benefit of Auto-Defrost and Drain is that a greater proportion of volatile solvents are collected for safe disposal, reducing VOC emissions.

EXALT™

Developed to help researchers conduct evaporative crystallisation studies, EXALT™ technology (patent pending) enables a wide range of solvents to be evaporated all at the same time, and at the same slow rate. For example, DCM and Toluene can be placed in the same system and evaporated such that both samples dry at the same time. The evaporation time can be controlled to range from 6 hours to 120 hours, or more as required.



EXALT
CONTROLLED CRYSTALLISATION

Mechanical data

Maximum speed	1250 rpm
Maximum G-force	500g
Drive system	Direct drive
Motor drive	Multi speed Inverter drive
Maximum imbalance	40g total

Vacuum system

Pressure display	0-1200mbar
Pressure control	Automatic 1mbar to atmosphere
System ultimate vacuum	0.05mbar
Bumping / foaming protection	Dri-Pure®

Temperature and control

Control range	Ambient +10°C to 60°C
Control accuracy	±2°C
Temperature sensing	Thermocouple
Display range	0°C to 60°C
End of method	Time or automatic
Process visualisation	Graphical display

Solvent compatibility

Boiling point range	40°C to 220°C at ambient
HCl	Resistant option required
Di-ethyl ether	Requires Inert Gas Purge option

Dimensions

Width x Depth x Height	660 x 690 x 830 mm
Weight	220kg

Services

Requires three of the following electrical supplies,

UK & Europe	230V (±10%), 50Hz, 13A
USA	120V (±10%), 60Hz, 15A
Japan	100V (±10%), 50Hz or 60Hz, 15A
USB A	For data upload and download

Maintenance

All seals are durable consumables and user replaceable. Easy access is provided to the pump, which can be maintained by trained users.

Safety

Conforms to BS EN 61010-1:2001 for laboratory equipment.
CE certified.

New nXDS6i vacuum pump

Provided with method specified pump purging to optimise vacuum and pump reliability.



Genevac Limited The Sovereign Centre Farthing Road Ipswich IPI 5AP UK
Tel: +44 (0) 1473 240000 Fax: +44 (0) 1473 742987

Genevac Inc 3538 Main Street Stone Ridge NY 12484 USA
Tel: (845) 255-5000 Fax: (845) 255-5338

salesinfo@genevac.co.uk www.Genevac.com/movie/Rocket



Printed in the UK on 100% recycled paper using vegetable-based inks.